

DEKOMA®



walt &
walt wallcovering

walt & walt wallcovering



Pelican 952



Sepia 518



Mauvewood 509



Biscuit 992




Dust 352




Clay 320




Spice 054




Oasis 315




Black 925



Chinchila 552



Onyx 923



Chrome 953



Azure 041



Turquize 962




Cameo 606



Asparagus 319



Olive 022



Palm 077



Lime 089



Terracotta 033



Watermelon 971



Sorbet 973



Magenta 602



Fire 105



Vino 047



Crocus 601



Dream 512




Indigo 993




Octopus 508




Orchid 919




Cobalt 193



Storm 905



Eggplant 926



Aubergine 515



walt





walt wall cover

name		WALT	WALT WALL COVER
composition		90% WO, 10% PL	-
composition surface		-	90% WO, 10% PL
composition backing		-	non woven
weight ±		550 g/m ²	730 g/m ²
usable width ±		150 cm	145 cm
roll lenght ± 5		25 m	25 m
thickness		3,5 mm	4 mm
abrasion resistance Martindale cycles	EN ISO 12947-2	80 000	80 000
colour fastness to light (1-8)	EN ISO 105-B02	4-5	4-5
colour fastness to rubbing (1-5)	EN ISO 105-X12	wet 4-5 dry 4-5	wet 4-5 dry 4-5
seam slippage	EN ISO 13936-2	↑ → 6 5,5 mm	↑ → - - mm
shrinkage	EN ISO 675	2%	-
pilling (1-5)	EN ISO 12945-2	4	4
flame retardant standards	EN 1021 US Cal. Bull. 117 UNI 9175	1,2 (when using PU FR foam 30-33 kg/m ³) Passed Class 1 (when using PU foam 35 kg/m ³)	- - -
acoustic properties	EN ISO 354 EN ISO 11654	α _w =0,45 D	-
type		upholstery decorative	wallcovering
cleaning		    	-

legend

WO - Wool
PL - Polyester

Colour shades may slightly vary from dye-lot to dye-lot.
For more details, visit our website dekoma.eu

					WALT
flame retardant	upholstery	decorative	acoustic		
				WALT WALL COVER	
wallcovering paste wall	straight match	strippable			

