

PRODUCT DATA SHEET



product name: **EARLY*****
collection: **UV PRO FLAT OUT**

Basic information

	Result
width total (+/-)	138 cm
width usable (+/-)	138 cm
weight (+/-)	271 g/m²
roll lenght (+/- 5m)	50 m
minimal order quantity	0.1 m
quantity of colours	6

Composition

acrylic	100%
---------	-------------

Technical data

	Norm	Result
abrasion resistance	EN ISO 12 947	26 000 Martindale cycles
colour resistance to light	EN ISO 105-B02	8
colour fastness to wet rubbing	EN ISO 105-X12	4-5
color fastness to dry rubbing	EN ISO 105-X12	4-5

seam slippage

EN ISO 13 936-2

warp 4 mm
weft 6 mm

pilling

EN ISO 12 945-2

4

Applications / parameters

curtains



upholstery



outdoor



oeke tex



water repellent



with mould-
resistant finish



Before you order

1. Colour shades may vary slightly between production lots.
2. Information presented on this website does not constitute a trade offer.
3. Product technical parameters contained in the safety data sheet are based on the manufacturer's data.
4. Data on maintenance (cleaning methods) pertains to the fabrics we sell, not to finished products comprising different elements.
5. Before cutting the fabric, please verify the quantity delivered, quality of materials and conformity with the order.
6. With complete rolls of textiles, the length may differ slightly from the value declared.
7. In case of any doubts regarding the use of our products, visit the TIPS section at www.dekoma.eu or contact us directly.
8. Colours of products presented on this website may differ from the actual colours.
9. Due to the specific character of the production process, the parameters provided i.e. width, height, grammage, and repeat may differ slightly from the values declared.