

## PRODUCT DATA SHEET



product name:**MASSI**

collection:**MASSI**

### Basic information

|                      | Result                     |
|----------------------|----------------------------|
| width total (+/-)    | <b>144 cm</b>              |
| width usable (+/-)   | <b>140 cm</b>              |
| weight (+/-)         | <b>700 g/m<sup>2</sup></b> |
| roll lenght (+/- 5m) | <b>22 m</b>                |
| quantity of colours  | <b>16</b>                  |

### Composition

|           |            |
|-----------|------------|
| elastane  | <b>1%</b>  |
| polyester | <b>99%</b> |

### Technical data

|                               | Norm            | Result                          |
|-------------------------------|-----------------|---------------------------------|
| abrasion resistance           | EN ISO 12 947-2 | <b>38 000 Martindale cycles</b> |
| colour resistance to light    | EN ISO 105-B02  | <b>5</b>                        |
| color fastness to wet rubbing | EN ISO 105-X12  | <b>4-5</b>                      |
| color fastness to dry rubbing | EN ISO 105-X12  | <b>4-5</b>                      |

|                                |                 |                                      |
|--------------------------------|-----------------|--------------------------------------|
| shrinkage wet                  |                 | <b>warp 1%</b><br><b>weft 0%</b>     |
| shrinkage dry                  |                 | <b>warp 1%</b><br><b>weft 0%</b>     |
| colour fastness to dry washing | EN ISO 105-D01  | <b>4</b>                             |
| seam slippage                  | EN ISO 13 936-2 | <b>warp 3 mm</b><br><b>weft 3 mm</b> |
| pilling                        | EN ISO 12 945-2 | <b>4-5</b>                           |
| snagging                       | BS 8479         | <b>5</b>                             |

## Flame retardant standards

Norm

Foam

Result

## Applications / parameters

upholstery



decorative



oeo tex



easy clean



pet friendly



## Maintenance



gentle wash at maximum 30 °c



do not bleach



tolerates ironing up to 110 °c



gentle dry deaning using hydrocarbones and tetrachloroethene



do not tumble dry



flat drying in shade

Iron on reverse.

## **Before you order**

1. Colour shades may vary slightly between production lots.
2. Information presented on this website does not constitute a trade offer.
3. Product technical parameters contained in the safety data sheet are based on the manufacturer's data.
4. Data on maintenance (cleaning methods) pertains to the fabrics we sell, not to finished products comprising different elements.
5. Before cutting the fabric, please verify the quantity delivered, quality of materials and conformity with the order.
6. With complete rolls of textiles, the length may differ slightly from the value declared.
7. In case of any doubts regarding the use of our products, visit the TIPS section at [www.dekoma.eu](http://www.dekoma.eu) or contact us directly.
8. Colours of products presented on this website may differ from the actual colours.
9. Due to the specific character of the production process, the parameters provided i.e. width, height, grammage, and repeat may differ slightly from the values declared.